

Technical Data Sheet

2012

Stain Repellent Impregnation H-D wet effect KOROLAN Protection

Product Characteristics

For indoor and outskirt areas – floors, walls and facades -
Solvent base, wet effect and environmentally friendly protection impregnation
for natural stone

Ingredients

According to EC recommendation
ph value n.a viscosity density :0,83g/cm³ for 20C Form :Fluid colour :yellow
Smell : characteristic on solvent water solubility : not water solubly

Chemical Properties:

Ready to use special impregnation for polish and for rough and sanded natural stone,
granite, marble etc.The product is stain-repellent, wetness and dirt-repellent
Self diffusion, UV-resistant (permanently), discoloration free, environmentally friendly and
bio-degradable. Wet look for all raw to finely polished natural stones. Especially intensive
on dark natural stones. No surface coating.

H-D special for dark, for highly priming stones z.B. Nero-Assoluto /StarGalaxy/ Impala/
Labrador / Nero Maquina u.ä.

Application:

Apply only if stone temperature is above 7 degrees Celsius

Don't use in direct sunlight and if the stone temperature is above 22 degrees Celsius
Floor heating must be deactivated.

The impregnating area must be residue free, clean, dry and greaseless.

That impregnating product is applied thinly and area-wide onto the cleansed and dry stone with a low
pressure sprayer, a sponge, soft cloth or a cleaning mop (micro fiber) in order to avoid drops and
cords. For highly priming stones – like - limestone – apply the product after drying for a second time.
During drying (approx. 6-8 hours) protect the area of wetness. Don't enter the area during the drying
period. Room must be ventilated.

Neighboring components like windows, aluminum, stainless steel, wood and carpets need to be
protected.

Recommendation: Test the area before you start with the application of the product.

Delivery: Plastic bottle/canister of 1 liter, 2.5 liters, 5 liters, 10 liters

Usage: 1 liter for 10 – 12 m²

Highly priming stones: 1 liter for 6- 8 m²

Shelf life (storage) original container must be closed and stored in a dry and frost protected area
Don't store below 5° Celsius or above 25° Celsius

Service Life: expiry date is indicated (approx. 1 year)

Safety, Ecology

Removal/ Adhesive Strength

For more information for transportation safety, storage and how to decontaminate and for the ecology consult the current safety data sheet. The afore mentioned declaration has been taken of the manufacturers' declaration according to the latest development and application technique.

As the usage and handling is outside our influence, no liability of the manufacturer can be derived from the technical data sheet. All additional information to the data sheet needs to be certified in writing by KORO. Our general terms and conditions are applied in all cases.

With the publication of this technical data sheet all former data sheets are losing their validity.

Identification Xi irritate eyes an skin.

Safety Advice

Please also consult the EC Safety data sheet. Keep out of reach of children. Always obey the safety advice.